isorocket®

PERMANENT SCAFFOLD ANCHOR FOR ETICS/ VCW/CAVITY WALL

MINI

USE ON MASONRY

MINI Masonry (100–179 mm)

Classification/system components

Designation:	Approved permanent scaffold anchor system for ETICS, ventilated curtain wall façade and cavity wall according to DIN 4426 (German standard). For use on masonry with a characteristic lead-bearing capacity of 5.0 KN of the strength class 28 in the format 3DF.
Add. feature:	for structure thicknesses from 100–179 mm
rocketplug:	Plastic frame plug (4 units)
rocketbase:	Load distribution plate, galvanised steel, 280 x 280 mm
rocketbody:	Anchor body, plastic (glass-fibre reinforced)
rocketbolt:	Eye-bolt, special steel, ø 18 mm
rocketseal:	Plug, plastic body with hex stainless steel insert
Art. number:	9.1.200

Accessories (available separately)

rocketglue:	fast-hardening composite glue for initial adhesion of the load distribution plate
Assembly set:	Available as Standard or Extended (for ETICS panels). Necessary special tools for assembly of the **isorocket**® permanent scaffold anchor

Product description:

The **isorocket**® permanent scaffold anchor **MINI Masonry** is an approved anchor system according to DIN 4426 (German standard) for external thermal insulation composite systems (ETICS), ventilated curtain wall façade (VCW) and cavity wall that protects the façade against damage right from the outset. **isorocket**® remains as a permanent, almost thermal bridge-free anchor point integrated into the façade, which means it can be reused at any time. Thanks to its ideal force dissipation, the **isorocket**® permanent scaffold anchor not only ensures a secure hold of the construction scaffold, it can also be applied for various uses in new buildings and also later. The extensive work required to fix damage to new façades, for instance damage often caused by conventional ring screws, is now a thing of the past. The **isorocket**® permanent scaffold anchor **MINI Masonry** is suitable for structure thicknesses of 100–179 mm on masonry. The permanent anchor system allows clean separation of the various trades and does not leave any mutual dependencies between the façade and scaffold construction.

Deutsches Institut für Bautechnik DIBt

Zulassungs-Nr. Z-21.8-2088



rocketbase (Load distribution plate) **rocket**plug (Wall plug) **rocket**body (Anchor body) **rocket**bolt (Eye-bolt) **rocket**seal (Seal)

Professional permanent scaffold anchor for ETICS, VCW and Cavity wall. Approved for use on masonry according to DIN 4426 (German standard) with ideal force dissipation. Remains permanently in the façade and can be reused at any time.

isorocket® GERÜSTANKER

isorocket GmbH · Wilhelm-Bunsen-Str. 5 · 49685 Emstek · www.isorocket.de

isorocket®

PERMANENT SCAFFOLD ANCHOR FOR ETICS/ VCW/CAVITY WALL

MINI

USE ON MASONRY

MINI Masonry (100–179 mm)

DIMENSIONS
rocketbody (Anchor body)



isorocket®
GERÜSTANKER

isorocket GmbH · Wilhelm-Bunsen-Str. 5 · 49685 Emstek · www.isorocket.de

isorocket®

PERMANENT SCAFFOLD ANCHOR FOR ETICS/ VCW/CAVITY WALL

MINI

USE ON MASONRY

MINI Masonry (100–179 mm)

DIMENSIONS
rocketbase (Load distribution plate)



isorocket®
GERÜSTANKER

isorocket GmbH · Wilhelm-Bunsen-Str. 5 · 49685 Emstek · www.isorocket.de

isorocket®

PERMANENT SCAFFOLD ANCHOR FOR ETICS/ VCW/CAVITY WALL

MINI

USE ON MASONRY

MINI Masonry (100–179 mm)

CAD SCREEN

The CAD data for this permanent anchor system are available for download at **www.isorocket.de**

isorocket®
GERÜSTANKER

isorocket GmbH · Wilhelm-Bunsen-Str. 5 · 49685 Emstek · www.isorocket.de